



[Tony Horton 10 Minute Trainer Completed Training Torrent](#)

It is important to specify the correct transport layer name before running the RKM SAP BW for the first time. Perform the following steps to identify the list of defined transport layers in your SAP landscape:

1. Log on in client 000 in the SAP System serving as the transport domain controller via transaction STMS.
2. Select **Overview > Transport Routes**. The Display Transport Routes dialog is displayed.
3. Select **Goto > Graphical Editor**.
4. To switch the mode, select **Configuration > Display <-> Change**.
5. Position the cursor on the SAP System.
6. Select **Edit > System > Change**. The Change System Attributes dialog is displayed.
7. Select the StandardTransport Layer tab.
8. Change the transport layer of the SAP System.
9. The result is the list of the different transport Layers.

By default, the RKM option `SAP_TRANSPORT_LAYER_NAME` is set to `SAP`. Ask your SAP basis admin which transport layer you should use. This transport layer name must be set on the `SAP_TRANSPORT_LAYER_NAME` RKM option. A wrong or invalid transport layer name will cause serious delays during the installation process.

Installing Oracle Data Integrator

Before starting with this project, you need to install and configure Oracle Data Integrator. See the *Oracle Fusion Middleware Getting Started with Oracle Data Integrator* and the *Oracle Fusion Middleware Installation Guide for Oracle Data Integrator* for more information.

Installing and Configuring the Oracle DB Target

This project uses an Oracle database engine as the target and as the staging area for the integration interfaces. You can download for example an Oracle XE database from the Oracle Technology Network (OTN). Install and configure this database.

This project targets an Oracle table that can be created using the following script:

```
-- Create demo target schema

CREATE USER ODI_SAP_DEMO IDENTIFIED BY ODI_SAP_DEMO DEFAULT TABLESPACE USERS
TEMPORARY TABLESPACE TEMP;
GRANT CONNECT, RESOURCE TO ODI_SAP_DEMO;

-- Create demo target tables
-- For ODS/DSO

CREATE TABLE ODI_SAP_DEMO.W_PURCH_DS (
  PO_GUID VARCHAR2(100),
  ORDER_ITEM_GUID VARCHAR2(100),
  ACC_ASS_GUID VARCHAR2(100),
  GUIDE_CONTRCT VARCHAR2(100),
  ORDER_QUANT NUMBER,
  NET_PRICE NUMBER,
```

[Tony Horton 10 Minute Trainer Completed Training Torrent](#)



624b518f5d